KYM05A HORIZONTAL BREAD SLICING MACHINE (SUPER AUTOMATIC)

GENERAL FEATURES:

.The slicing process is done automatically after the bread is placed in the inlet chamber and the top cover is closed.

. For automation, there are for mechanical switches: 1 pc under the top cover, 1 pc at the cutting start point, 1 pc at the cutting end point and 1 pc sliced bread detection point.

. Bread placing and delivery sections are designed with security compartments.

. Modern aesthetic design.

. Easily movable with wheels.

. 304 quality stainless steel on the contact surface of the bread.

. The body of the machine is painted with electrostatic paint.

. There is a crumb drawer at the bottom of the machine.

. It slices whole bread up to a maximum of 2.5 kg.

. Cutting process is made in the desired slice thickness, from 8mm to 18 mm. Upon specific demand this thickness may be provided with bigger sizes.

. Standard blade intervals are installed as 18 mm.

. It is produced in CE standards.

. With bread packaging apparatus.

OBTIONNEL:

. Specificaly designed slicing machines for other than bread; etc for halva, meat, cake, soap are available upon order.

TECHNICIAL SPECIFICATIONS	
Capacity	300 breads/hour
Width	67cm
Lenght	75cm
Height	125cm
Max. Bread Size	33x48x18cm
Motor	0.37Kw
Electricity Supply	220 Volt monophase
Machine Weight	160 Kg

ADDITIONNEL :

. Specific electrical devices suitable for the electrical network specifications of the user country can be used at the machine. The buyer should specify this situation at the time of price quotation demand.

. The manufacturer reserves the right to make changes on the machine without notice.

. 7/24 Technical Service Assistance

. 2 years warranty period.

Factory Adress: Meclis Mah. Teraziler Cad. Perpim Sanayi Sitesi A.Blok 31/A 24-25-29
Showroom Adress : Meclis Mah. Teraziler cad. No: 52/B Sancaktepe / İSTANBUL / TURKEY
Tel: 00 90 216 415 58 25 Mobil: 00 90 533 294 58 25
Email: ihracat@kayamaktek.com.tr Web: www.kayamaktek.com.tr